

SCB-6909

Desktop Network System

AEWIN Technologies Co., Ltd.

Fanless Desktop Intel Celeron N3350 and Intel® ATOM™ x5-E3930 Network system, Intel® i211AT 4GbE ports w/one pair bypass, 2GB onboard RAM, 8GB eMMC, 2USB, mini-PCIe, console and micro USB/console



Features

- Compact Fanless Network System
- Ideal Noiseless System for Silence environments Use
- Intel® Apollo™ Lake Processor, support Atom x5-E3930 and Celeron® N3350
- DDR3L 1866MHz memory, max support 2GB
Max 4 RJ45 GbE ports
- eMMC flash, support up to 64GB (default 8GB)
- Expansive I/O with two USB 2.0, one mini-PCIe socket and one Console port



Introduction

The SCB-6909 is a fanless desktop hardware platform designed for network service applications which is a noiseless system ideal for silence environments use. Built with Intel® Embedded IA components with warranty of longevity, supports Intel® Atom™ /Celeron® Apollo Lake-I low voltage processors.

The SCB-6909 supports 2GB on-board DDR3L memory. In order to provide the best network performance and best utilization, the storage interfaces include eMMC, and it affords four Copper GbE on rear-panel. The rear panel also has two USB 2.0 ports, one RJ-45 console port or micro USB console port. The front panel has LED indicators that monitor power and storage device activities for local system management, maintenance and diagnostics. In addition, the SCB-6909 supports one mini-card socket for expansion purpose. The networking system is RoHS, FCC and CE compliant.

Specifications

Processor System

CPU	Intel® Atom™ Processor x5-E3930 or Intel® Celeron® Processor N3350
------------	--

BIOS	AMI® UEFI BIOS
-------------	----------------

Memory

Technology	Un-buffered and Non-ECC DDR3L 1600/1866MHz onboard memory
-------------------	---

Capacity	Max. 2GB
-----------------	----------

Ethernet

GbE Ethernet	4x Copper GbE ports, Intel® I211AT, PCIe x 1
---------------------	--

LAN Bypass	1x Pair
-------------------	---------

Storage

eMMC	eMMC 5.1 8GB, up to 64GB
-------------	--------------------------

SSD	2.5" SSD(Optional)
------------	--------------------

I/O

USB	2x external USB2.0
------------	--------------------

Serial	1x RJ45 Console port (COM1) 1x micro-USB Console port (USB)
---------------	--

Power Supply

Watt	24W power adapter
-------------	-------------------

Mechanical and Environment

Form Factor	Desktop
--------------------	---------

LED	WiFi LAN LED (Green) Status/bypass (Green/Red) One Power LED (Green/Red) One HDD LED (Blue) 4x pairs LEDs for four Ethernet ports speed and Active/Link
------------	---

Dimension (W x D x H)	232mm (W) x 115mm (D) x 44mm (H) (9.1" W x 4.5" D x 1.7" H)
------------------------------	--

Operating Temperature	Operating: 0 ~ 40°C (32 ~ 104°F)
------------------------------	------------------------------------

Storage Temperature	-20 ~ 75°C (-4 ~ 167°F)
----------------------------	-------------------------

Humidity	10 ~ 85% relative humidity, non-operating, non-condensing
-----------------	---

Weight	820g
---------------	------

Certification	CE/FCC
----------------------	--------

* Note : All specifications are subject to change without prior notice

▼ Packing List

- 1x SCB-6909 unit
- 1x power adapter
- 1x CD (Manual, Quick installation guide, Utility driver)

▼ Ordering Information

Standard	
SCB-6909A	Fanless Desktop Intel Celeron Processor N3350 Dual Core Network system, 4GbE ports, 2GB on-board RAM, 8GB eMMC, 2USB, mini-PCIe, console, micro USB/console
SCB-6909B	Fanless Desktop Intel Atom Processor X5-E3930 Dual Core Network system, 4GbE ports, 2GB on-board RAM, 8GB eMMC, 2USB, mini-PCIe, console, micro USB/console

* Note : All specifications are subject to change without prior notice

