

# BIS-5102

General Purpose Server

## AWIN Technologies Co., Ltd.

2U rack-mount General Purpose Server with single 3rd Intel® Xeon® Scalable Processors(Ice Lake-SP) and Intel® PCH C621A workstation, support 8x DDR4 RDIMM (up to 3200MHz), 12 bays 3.5" Hot-Swap SAS/SATA HDD, IPMI, USB 3.0/2.0, 2x 1GbE, 1x Console, 2x M.2, Redundant PSU



### Features

- 2U Rack-mountable Workstation System
- Single 3rd Gen Intel® Xeon® Scalable Processors up to 205W TDP
- 8x DDR4 RDIMM/LRDIMM Memory slots
- Support 5x PCIe HHHL PCIe card
- Up to 2x 80PLUS Platinum Certified 550W CRPS



### Description

BIS-5102 is a rack-mount 2U workstation system with single 3rd Gen Intel® Xeon® Scalable Processor based on the Ice Lake-SP platform. This new generation of Xeon processors brings significant improvement in core count and IPC, elevating the overall performance to a new level. With total of 64x PCIe Gen4 lanes, it offers enough bandwidth for any PCIe based accelerators. BIS-5102 is designed to accommodate 2x PCIe Gen4 x16, plus 3x more with PCIe Gen4 x8 slots. This allows the BIS-5102 to flexibly support various add-on card configuration. With on-board BMC, you can enjoy the ease of management of server class hardware. Redundant CRPS power supplies ensure the highest availability available for this server.

### Specifications

#### ▼ Processor System

CPU	Support Single 3rd Gen Intel® Xeon® Scalable Processor (Ice Lake-SP)
Chipset	Intel® C621A
CPU	AMI 64Mb SPI BIOS

#### ▼ Memory

Technology	Total 8x RDIMMs (8x memory channels) ECC & Registered DDR4 2666/2933/3200MHz memory
Capacity	Validated up to 256GB (with 32GB 3200MHz RDIMMs)

#### ▼ Expansion

Onboard Expansion Slots	2x PCIe Gen4 x16 slots 3x PCIe Gen4 x8 slots
-------------------------	---

#### ▼ I/O

USB	2x USB 3.0 (Front I/O) 1x USB 3.0 (Rear I/O)
Serial	1x RJ45 Console port (COM 1) 1x VGA port

#### ▼ Ethernet

GbE Ethernet	2x 1GbE RJ45 ports + 1x MGMT/IPMI port
--------------	--

#### ▼ Storage

SATA/SAS	12x 3.5" Hot-Swap SAS/SATA Bays
M.2	2x M.2 (2280 M-key) PCIe Gen3 x2

#### ▼ Power Supply

Watt	Redundant 550W CRPS
------	---------------------

#### ▼ Mechanical and Environment

Form Factor	2U Rack-mountable Desktop Workstation
LED	1x Power Button/LED 1x Reset Button 1x HDD LED 1x ID Button/LED
Dimension (W x D x H)	438mm(W) x 558mm(D) x 87mm(H)
Operating Temperature	Operating: 0 ~ 40°C ( 32 ~ 104°F )
Storage Temperature	0 ~ 75°C (32 ~ 167°F)
Humidity	10 ~ 85% relative humidity, non-operating, non-condensing
Certification	CE/FCC

#### ▼ Packing List

- 1x BIS-5102 unit