

# SCB-7911

Value Network Appliance

## AEWIN Technologies Co., Ltd.

1U Network System with Intel Alder Lake-N or Amston Lake-C processor, 1 x DDR4 SO-DIMM, 5 x 1GbE RJ45 (Intel I210-AT) with 1 x Bypass, 1 x 1 GbE SFP (Intel I210-IS), 2 x USB 3.0, 1x 2.5", 1 x mSATA, PCIe x 4 connector, eMMC 5.1



### Features

- Support Single Intel Celeron/Pentium/Atom Processor (Alder Lake-N or Amston Lake-C), BGA1264
- 1x DDR4 SO-DIMM memory, up to 3200 MHz
- 5x 1GbE RJ45 ports, 1x 1GbE SFP port
- 1x Expansion Module bay (PCIe x4)
- 1x 2.5" SATA, 1x mSATA, 1x eMMC 5.1

### Description

SCB-7911, powered by Intel Alder Lake N or Amston Lake-C featuring upgraded computing performance with low power consumption. SCB-7911 supports DDR4 memory with up to 16GB, 3200MHz and is designed with improved energy efficiency for networking solutions.

SCB-7911 has up to 5x 1GbE ports with 1 pair of Gen3 Bypass, 1x SFP, 1x Expansion Module bay (PCIe x4). In addition, SCB-7911 offers 2x USB 3.0, and multiple storage options (1x eMMC, 1x SATA3 2.5" SATA SSD/HDD, and 1x mSATA).

Regarding security support, it has Intel AES-NI for crypto acceleration and TPM for protected data/keys/identity. It is also with many hardware-based secure technologies for system reliability including Intel TEE (Trusted Execution Environment) for sensitive data protection, and Intel OS Guard plus Intel Boot Guard for platform integrity.

### Specifications

#### Processor System

|         |  |
|---------|--|
| CPU     | Intel® Celeron® Pentium® Atom® (Alder Lake-N or Amston Lake-C) |
| Chipset | SOC Integrated   |
| BIOS    | AMI UEFI BIOS  |

#### Memory

|            |                    |
|------------|--------------------|
| Technology | DDR4 up to 3200MHz |
| Capacity   | Max Up to 16GB     |

#### Expansion

|                         |                      |
|-------------------------|----------------------|
| Onboard Expansion Slots | 1x PCIe Gen3 x4 slot |
|-------------------------|----------------------|

#### I/O

|        |                 |
|--------|-----------------|
| USB    | 2x USB 3.0      |
| Serial | 1x RJ45 console |

#### Ethernet

|              |  |
|--------------|--|
| GbE Ethernet | 6x RJ45 w/ one pair of Bypass (1x optional 2.5GbE port and 1x 1GbE SFP port) |
| LAN Bypass   | 3 Pairs Gen3   |

#### Storage

|       |                       |
|-------|-----------------------|
| SATA  | 1x 2.5"               |
| mSATA | 1x mSATA              |
| M.2   | eMMC 5.1, up to 128GB |

#### Power Supply

|      |                           |
|------|---------------------------|
| Watt | 65W build-in power supply |
|------|---------------------------|

#### Mechanical and Environment

|                       |   |
|-----------------------|---|
| Form Factor           | 1U rack-mount   |
| LED                   | 1x Power LED (Green)<br>1x HDD LED (Red)<br>2x Status LED (Green/Yellow via programmable GPIO)<br>3x Bypass LED (Green) |
| Dimension (W x D x H) | 440mm(W) x 269 mm(D) x 44mm(H)  |
| Operating Temperature | Operating: 0 ~ 40°C ( 32 ~ 104°F )  |
| Storage Temperature   | -20 ~ 75°C (-4 ~ 167°F)   |
| Humidity              | 10 ~ 85% relative humidity, non-operating, non-condensing   |
| Weight                | 4.5 kg  |
| Certification         | CE/FCC  |

#### Packing List

- 1x SCB-7911 unit
- 1x power cord

## Ordering Information

SCB-7911A 1U Network System with Intel Alder Lake-N i3-N305 processor, 1 x DDR4 SO-DIMM, 5 x Copper GbE (Intel I210-AT), 1 x fiber GbE (Intel I210-IS), 2 x USB 3.0, 1 x SATA, 1 x mSATA, PCIe x 4 connector, eMMC 8G, 1 x Bypass

## I/O

